



**ProSwitch® GSM**  
**Managed Gigabit Switch**  
**with PoE Model**

**Model: GSM3128**  
**GSM3128-POE**

**Key Highlights**

- ▶ 24 10/100/1000Base-TX ports
- ▶ 4 SFP slots for 100Base-FX or 1000BaseSX/LX modules
- ▶ 4 XFP slots for 10GbE modules
- ▶ 28 useable ports
- ▶ Energy Efficient
  - IEEE 802.3az
  - Uses low-power technology
  - Adjusts signal strength based on cable length
- ▶ PoE Functions
  - Supports IEEE 802.3at high power PoE
  - Up to 30 watts of power per port
  - Connect IP telephones, cameras and wireless APs
- ▶ Advanced Network Management
  - IPv4 and IPv6 support
  - SNMP
  - LLDP
  - S-Flow
  - SSL/SSH
  - ACLs
  - Guest VLANs
  - IP Source Guard
  - RADIUS/TACACS
  - Private VLAN Edge (PVE)
- ▶ Convection cooled for quiet operation
- ▶ Backed by Waters' limited lifetime warranty

**WATERS NETWORK SYSTEMS**  
www.watersnet.com

Corporate Headquarters 7401 Metro Blvd., Suite 560 Edina, MN 55439 Toll Free: 800.862.3894 Phone: 952.831.5604 Fax: 952.831.5605	Manufacturing 945 37th Avenue, NW Rochester, MN 55901 Toll Free: 800.328.2275 Phone: 507.285.1951 Fax: 507.285.1952
---	--

**GSM3128 Ethernet Switch**  
10/100/1000Mbps Switch



**GSM3128**

**Waters Network Systems' GSM3128** switches deliver reliable intelligent 10/100/1000Base-TX connectivity services from the core to the edge. The GSM3128 models provides the application intelligence, manageability and performance to support IP data, voice and video deployment for today's most demanding LAN applications. Four 10GbE slots are available for upgrades to 10 Gigabit speed.

**Features and Benefits**

- **Device management software.** All models incorporate an intuitive, web-based interface used to access the management functions. CLI access is also available.
- **Link Layer Discover Protocol (LLDP).** The GSM3128 supports IEEE 802.1ab standards based discovery protocol and provides vendor-independent device discovery. LLDP not only simplifies switch deployment and location of devices, but it can also be used as a troubleshooting, monitoring and firmware management tool.
- **QoS support.** The GSM3128 includes embedded QoS intelligence to prioritize services such as voice, easily unified deployments and helps ensure consistent network performance for all services.  
  
The voice VLAN capabilities allow any IP phone to be plugged into the IP telephony network and receive an immediate dial tone. The switch will configure the device with network specific VLAN and QoS parameters to simplify voice traffic prioritization.
- **Network security.** The GSM3128 provides 802.1x which enables user authentication for each network access attempt. Port security allows you to limit the number of MAC addresses per port for better control. Static MAC addresses can be defined for each port to ensure only registered workstations are allowed access. By enabling both of these features, you can establish an access mechanism based on user and workstation identities, as well as control the number of access stations.
- **Power savings features.** Green power technology is delivered by the GSM3128 with the Energy Efficient Ethernet (EEE) option. EEE reduces power usage when there is a very low traffic utilization (or no traffic).

EEE works by powering down circuits when there is no traffic, and automatic PoE power shutoff is invoked when a line is down or set with the PoE scheduling function. Embedded intelligence is used to adjust power strength based on cable length.



# GSM3128-Ethernet Switch

## ORDERING INFORMATION

Model	Description
<b>10/100/1000Mbps Managed Ethernet Switch</b>	
GSM3128-4C-10G	28-port managed switch with 24 10/100/1000Base-TX ports plus 4 slots for 100Base-FX or 1000BaseSX/LX SFP fiber modules. Plus 4 ports for 10GbE XFP fiber modules (28 useable ports)
GSM3128-4C-10G-POE	28-port managed switch with 24 10/100/1000Base-TX PoE ports plus 4 slots for 100Base-FX or 1000BaseSX/LX SFP fiber modules. Plus 4 ports for 10GbE XFP fiber modules (28 useable ports)

### Fiber Modules

SFP-100FX-LC	1 port 100Base-FX MM fiber module with LC connector
SFP-100FX-LC-SM10	1 port 100Base-FX SM (10km) fiber module with LC connector
SFP-100FX-LC-SM40	1 port 100Base-FX SM (40km) fiber module with LC connector
SFP-1000SX-LC	1 port 1000Base-SX MM fiber module with LC connector
SFP-1000LX-LC10	1 port 1000Base-LX SM (10km) fiber module with LC connector
SFP-1000LX-LC30	1 port 1000Base-LX SM (30km) fiber module with LC connector
XFP-10GbE-SRLC	1 port 10G MM XFP fiber module with LC connector
XFP-10GbE-LRLC-10	1 port 10G SM (10km) XFP fiber module with LC connector

## SPECIFICATIONS

### OPERATIONAL CHARACTERISTICS:

MAC Address Table

▶ 32K

Switching Capacity and Forwarding Rate

▶ 95.23Mpps (64-byte packets)

▶ 128Gbps switching capacity

▶ Frame size supported up to 9Kb

### POWER SAVINGS FEATURES

▶ Energy detect

▶ Cable length detection

### MANAGEMENT FUNCTIONS:

▶ Web-based and console

▶ Remote management SNMP

▶ Link layer discovery protocol (LLDP) support

▶ Port setting for duplex and speed

▶ Port trunking (up to 14 groups; up to 8 ports per group)

▶ VLANs

▶ Port based

▶ Tag based

▶ MAC based

▶ Management VLAN

▶ Private VLAN Edge (PVE)

▶ Port mirroring

▶ DHCP Option 82

▶ SNMP v1, v2c and v3

▶ IGMP v1, v2 and v3 snooping

▶ IGMP querier

▶ IGMP proxy

▶ MLD v1 and v2 snooping

▶ SSH v1 and v2

▶ SSL

▶ 802.1x RADIUS authentication

▶ Port security

▶ IP source guard

▶ RADIUS / TACACS+ authentication

▶ Storm control

▶ ACLs

▶ QoS supports 8 hardware queues

▶ Supports strict priority and weighted round-robin (WRR); queue assignment based on DSCP and class of service

▶ IPv4

▶ IPv6 (Web/SSL, Telnet/SSH, ping, SNMP, TFTP, SNMP, Syslog)

▶ Rate Limiting (ingress/egress)

▶ Dual image supported

▶ GARP/GVRP

▶ RMON

▶ Firmware upgrade

▶ s-Flow (RFC 3176)

▶ UpnP

▶ CIDR

### NETWORK STANDARDS:

▶ IEEE 802.1d/w

▶ IEEE 802.1p

▶ IEEE 802.1q

▶ IEEE 802.1s

▶ IEEE 802.1x

▶ IEEE 802.3

▶ IEEE 802.3ad

▶ IEEE 802.3az

▶ IEEE 802.3ab

▶ IEEE 802.3at (GSM3128-POE)

▶ IEEE 802.3u

▶ IEEE 802.3x

▶ IEEE 802.3z

### GSM3128-POE FUNCTIONS:

▶ PoE-PSE activity LED indicator

▶ Auto detect powered devices and consumption levels

▶ Supports per port power consumption monitoring and per port priority setting

▶ Supports per port PoE state and power priority setting

### EMI/SAFETY COMPLIANCE:

FCC Part 15 (CFR47) Class A & CE Mark

Approval UL60950 CSA 22.2

### NETWORK CABLE CONNECTORS:

RJ45 shielded female ports

▶ 10/100Mbps: CAT5 UTP or better

▶ Multimode or singlemode with LC connectors

### POWER SUPPLY:

Internal power supply

Input Voltage

▶ 100 to 240 VAC, 50 to 60Hz

Power Consumption

▶ GSM3128-POE: 200W

### OPERATING ENVIRONMENT:

Cooling Method: Convection

Ambient Temperature:

▶ 32° to 104°F (0° to 40°C)

Storage Temperature

▶ -4° to 158°F (-20° to 70°C)

Ambient Humidity:

▶ 10% to 90% (non-condensing)

### MECHANICAL:

Enclosure:

▶ Mounting kit available

### PHYSICAL CHARACTERISTICS:

GSM3128-POE Dimensions:

▶ 17.4 x 1.73 x 12 in

▶ 442 x 44 x 300mm

GSM3128-POE Dimensions:

▶ 17.4 x 1.73 x 15 in

▶ 442 x 44 x 385mm

Weight:

▶ 5lbs (2.4kg)

### WARRANTY:

Limited Lifetime